

ASUS Fanless Chromebox CF40

ASUS Fanless Chromebox CF40 delivers performance and connectivity to build an efficient digital signage or kiosk



Celeron N4500
Intel Processor



LPDDR4X
Memory



PCIe 3.0x4
M.2 SSD



Google Play
Support



Automatic
Update



Google
Admin Console



PD Input



Wi-Fi 6
AX201



Kensington
Lock

Cost-efficient performance for any workplace

- Built-in with the Intel® Celeron® N4500 Processor
- Intel® UHD Graphics

Built for kiosk & digital signage

- Fanless design providing silent operation and lower maintenance
- Dual HDMI ports with CEC support
- USB Type-C supports both display output and Power Delivery input
- Up to 6 USB ports (5 x USB-A, 1 x USB-C)

Simplified IT management

- Always up to date operating system
- Centralized cloud management via Google Admin Console
- Secure by design with multilayered defense

ASUS Fanless Chromebox CF40

Overview:



Accessories list:



- Power Cord
- AC Adapter (80cm)
- Quick Start Guide & Warranty Card
- VESA Mount Kit (Optional)
- Keyboard & Mouse for Chrome OS (Optional)

Feature table:

Power	Security	Reliability	Reliability	Others
PD input	Kensington lock	24/7 Durability Test	Military-grade Durability	Fanless



ASUS Fanless Chromebox CF40

Model		ASUS Fanless Chromebox CF40
OS		Chrome Enterprise or ChromeOS
CPU		Intel® Celeron® Processor N4500
Chipset		Integrated
Graphics		Intel® UHD Graphics
Memory		LPDDR4x 4G/8G/16G
Storage		eMMC 32G/64G/128G
Wireless Network		Intel® Wi-Fi 6 AX201, 2x2, and Bluetooth® 5.2* (* Bluetooth version depends on OS support)
LAN		Realtek Gigabit Ethernet, 10/100/1000 Mbps
Interface	Front I/O	3 x USB 3.2 Gen1 Type A / 1 x Audio Jack (Mic / Headphone Jack)
	Rear I/O	2 x USB 3.2 Gen1 Type-A / 1 x USB 3.2 Gen1 Type-C (DP/PD in) 2 x HDMI / 1 x Gb LAN Port / 1 x DC-in / 2 x Wi-Fi antenna 1 x Recovery button / Kensington slot
Power Supply		65W Power Adapter (19Vdc, 3.42A)
Physical	Dimension	166.2 x 119.7 x 33.9 mm (0.67L)
	Weight	775g
Accessories		AC Adapter + Power Cord Warranty Card Quick Start Guide Wi-Fi antenna VESA Mount (Optional) Keyboard+Mouse (Optional)
Temperature	Operating	0°C~50°C
	Storage	-40°C~85°C
Humidity		0%~95% Relative Humidity
Certificates		BSMI / CB / CE / FCC / UL / Energy Star / C-Tick / WiFi / RF / VCCI